

Assistant Commissioner for Patents Washington, D.C. 20231

Docket No.: 041-479-L	P <u></u>
Date: November 2, 2000	
	S. 4.
	⇒ <u>2</u>
	26°
	<i>8,</i> □ =='

NEW APPLICATION TRANSMITTAL

Transmitted herewith for filing is the patent application of Inventor(s):

LEV SMORODINSKY

Note: A patent must be applied for in the name(s) of all of the actual inventor(s). 37 CFR 1.41 For:

METHOD FOR SERVER METAFARM CONFIGURATION OPTIMIZATION

Enclose	ed are:		
1. The Papers Required for Filing Date Under 37 CFR 1.53(b):			
	28	Pages of specification	
	1	Pages of Abstract	
	5	Pages of claims	
	4	Sheets of drawings	
		formal	
		X informal	
	In addition to	the above papers, there is also attached:	
		Pages of an amendment	
		CERTIFICATION UNDER 37 CFR 1.10	
with the	United States ressee" Mailing	is paper (along with any paper referred to as being attached or enclosed) is being deposited Postal Service on this date, <u>November 2, 2000</u> , in an envelope as "Express Mail Post Office g Label Number <u>EL070486540US</u> addressed to: Box Patent Application, Assistant ents, Washington, D.C. 20231.	
		Patti S. Preddy (Type or print name of person mailing paper) Atti S. Preddy (Signature of person mailing paper)	
NOTE:	Each paper or f	fee referred to as enclosed herein has the number of the "Express Mail" mailing label placed thereon prior R 1.10(b).	

2.	Declar	ation or oath				
	X	Enclosed				
		X	original			
		executed by ((check all applicable boxes)			
		X	inventors(s)			
			legal representative of inventor(s) 37 CFR 1.42 or 1.43			
		-	joint inventor or person showing a proprietary interest on behalf of inventor who refused to sign or cannot be reached.			
			This is the petition required by 37 CFR 1.47 and the statement required by 37 CFR 1.47 also attached. See item 7 below for fee.			
		_ Not enclosed				
	NOTE:	Where the filing is a co declaration must be filed.	mpletion in the U.S. of an international application under 35 U.S.C. 371(c)(4), the			
		Application is made by a person authorized under 37 CFR 1.41(c) on behalf of all of the above-named inventors(s). The declaration or oath, along with the surcharge required by 37 CFR 1.16(e) can be filed subsequently.				
	NOTE:	NOTE: It is important that all the correct inventors(s) are named for filing under CFR 1.41(c) and 1.53(b).				
		Showing that 37 CFR 1.14	the filing is authorized. (Not required unless called into question. I/d).			
3.	Langua	Language				
	X	English				
		non-English				
	NOTE:	An application including a	a signed oath or declaration may be filed in a language other than English. A verified			
	CFR 1.52(d).	English translation of the non-English language application and the processing fee of \$20.00 required by 37 1.17(K) is required to be filed with the application or within such time as may be set by the Office. 37 CFR				
	NOTE:	IOTE: A non-English oath or declaration in the form provided or approved by the PTO need not be translated 37CFR1.60(b).				
		A verified Eng	lish translation of the specification is attached.			
4.	Assign	ment				
	X_	An assignmer	nt of the invention to <u>UNISYS CORPORATION</u>			
5.	Certifie	ed Copy				
	•	A certified cop	by of application(s) from which priority is claimed.			
	NOTE:	Must be referred to in oat	h or declaration. 37CFR1.55 and 1.63.			

6. **Fee Calculation**

CLAIMS AS FILED

Number Filed	Number Extra	Rate	Basic Fee \$710.00
Total Claims -1220=	-0- X	\$ 18.00	-0-
Independent Claims -13=	-0- X	\$ 80.00	-0-
Multiple dependent claim(s) if any -0-	-0- X	\$270.00	-0-

	Amendment c	anceling extra claims enclosed	
	Amendment d	eleting multiple dependencies enclosed	
	Fee for extra	claims not being paid at this time	
		s are not paid on filing, they must be paid or the claims canceled by ame eriod set for response by the Patent and Trademark Office in any r	
	CFR 1.16(d)		
Fili	ing Fee Calculation		\$ <u>710.00</u>
Small Entit	y Statement		
	verified staten	nent that this is a filing by a small entity under 37 CFR 1.9 and 1.3	27 is
	attached.		
	Filinç	g Fee Calculation (50% of above)	\$
Fee Payme	nt Being Made At T	his Time	
	Not Enclosed		
		No filing fee is to be paid at this time. This and the surcharge	e required
		by 37 CFR 1.6(e) can be paid subsequently.	
NOTE: W	nere the filing is comple	etion in the U.S. of an international application, the fee must be paid.	
X	Enclosed		
	X	basic filing fee	\$ <u>710.00</u>
	X	recording assignment	\$ <u>40.00</u>
		(40.00 37CFR 1.21(h)(j)	
		petition fee for filing by other than	
		all the inventors or person on behalf	
		of the inventor where inventor refused to sign	
		or cannot be reached. (\$130.00 37 CFR 1.47 and 1.17(h)	\$

			for processing an application	II WILL	
			a specification in a non-Eng	ılish language	
			(\$20.00; 37 CFR 1.53(d) an	d 1.17(k)	\$
			processing and retention fee	e	
			\$100.00; 37 CFR 1.21(I)		\$
	NOTE:	complete the application indicate that in order to	es a fee for processing and retaining pursuant to 37 CFR 1.53(d) and this o obtain the benefit of a prior U.S fee of §1.21(I) within one year from r	s, as well as the changes to S. application, either the b	37 CFR 1.53 and 1.78 pasic filing fee or the
			Total fees enclosed		\$ <u>750.00</u>
١.	Method	l of Payment of Fees			
		_ check in the a	amount of \$		
	X_	charge Accou	unt No. <u>19-3790</u> in the amount of	f \$ <u>750.00</u> . A duplicate of	this transmittal is
		attached.			
	NOTE:	Fees should be itemized	in such a manner that it is clear for v	vhich purpose the fees are p	oaid. 37 CFR 1.22(b)
0.	Author	ization to Charge Addi	tional Fees		
	NOTE:	If no fees are to be paid of	on filing, the following items should n	ot be completed.	
	WARNIN claims, t		are to be checked, then accurated unexpected high charges.	ely count claims, especiali	ly multiple dependent
	X_	The Commiss	sioner is hereby authorized to ch	arge the following addition	onal fees which
		may be requi	re to Account No. 19-3790 .		
		X	37 CFR 1.16 (filling fees and	d presentation of extra cla	aims)
			37 CFR 1.17 (application pr	ocessing fees)	
			37 CFR 1.18 (issue fee at o	or before Mailing of Notice	e of Allowance,
			pursuant to 37 CFR 1.31(b)	ı .	
	NOTE: the	37 CFR 1.28(b) requires applicationprior to pay.	"Notification of any change in loss oissue fee."	f entitlement to small entity	status must be filed in
1.	Instruc	tions As To Overpaym	ent		
	X_	credit Accour	nt No. <u>19-3790</u>		
		refund		_	
			3	OU LAttorney	J. Kozak
Reg. N	lo. 24,265		<u>.</u>	Alfred W. Kozak	
al Na	(858) 45	1_1615	(Type or print name of att	torney)
i ei 140	. (858) 45	1- 10 10	1	Unisys Corporation 10850 Via Frontera, MS 1 San Diego, CA 92127	1000

Docket 041-479-L

TITLE: METHOD FOR SERVER METAFARM CONFIGURATION OPTIMIZATION

FIELD OF THE INVENTION:

This invention relates to data processing systems of the type which include a Server Metafarm that Farms one or more Server that application programs for multiple clients (users); and more particularly, this invention relates to methods for optimizing the "Server Metafarm size" by balancing a number of Server Farms and availability requirements in the above type of data processing systems.

10

15

20

CROSS-REFERENCES TO RELATED APPLICATIONS:

This is application related to co-pending applications, USSN 08/550,603 entitled "Estimator Program for Estimating the Availability of an Application Program That Runs in a Cluster of at Least Two Computers"; USSN 09/443,926, entitled "Method for Estimating the Availability of an Operating Server Farm", and USSN 09/474,706, entitled "Method for Server Farm Configuration Optimization" which applications are incorporated herein by reference.

BACKGROUND OF THE INVENTION:

The co-pending application "Estimator Program for Estimating the Availability of an Application Program That Runs in a Cluster of at Least Two Computers" referenced above involves an estimator program to perform method steps for estimating the availability of an application program that runs on any "server" in a cluster of at least two servers. By "availability of an application program" is meant the probability that at any particular time instance, at least one of the servers in a cluster (farm) will actually be servicing requests from external workstations able to use the application program.

one embodiment, the so-called estimator 25 program begins by receiving input parameters include (i) multiple downtime periods for each computer in the cluster (farm) that occur at respective frequencies due to various downtime sources, and (ii) an

15

20

30

application "failover" time period for switching the running of the application program from any one computer to another computer which is operable. From these input parameters, the described estimator program estimates first and second annual stoppage times, then determines the availability of the application program on the cluster of computers which is derived from the sum of the first and second annual stoppage times.

Thus, as discussed, the estimator program of the previously-described invention estimated a first annual stoppage time for the application program due solely the concurrent stoppage οf all to as a function of the ratio of a single computer virtual downtime period over the single computer virtual time between stops. Then subsequently, the estimator program was used to estimate a second annual stoppage time for the application program, due solely to the switching for running the application program from one computer to another computer as a function of the single virtual stoppage rate and the application failover time period. From this, the estimator program determined the availability of the application program on the cluster of computers by deriving the sum of the first and second annual stoppage times.

The estimator program method was based on the assumption that "application availability" was to be determined from four factors which were:

- (i) single-server hardware reliability;
- (ii) maintenance, support, and service
 strategies;

20

25

(iii) user application and environment;

(iv) failover or system reconnection mechanism and application recovery mechanism.

The prior estimation parameters which were described in the co-pending application USSN 08/550,603 did not take into consideration the total number of operating Server Farm clients and the normal single server workload of users involved with each single server. Further, this earlier application did not provide a recommendation or estimate regarding the number of servers required in the Server Farm (or cluster) which would meet the customers' performance and redundancy level requirements, nor did it establish an optimum farm configuration.

The method of the co-pending application USSN 09/443,926, entitled "Method for Estimating the Availability of an Operating Server Farm" extended the area of the original method application for Server Farms designed to serve user communities with a required particular number of customers . This method involving the Server Farm size and availability calculations is based on (1) the single server parameters such as (a) the meantime to failure (MTTF), (b) the meantime to repair (MTTR), and (c) the single server application performance benchmarks, and (2) individual customer preferential requirements, involving (a) the total number of Server Farm application users and (b) a desirable redundancy level.

This estimation method for availability uses

30 the following definition of Server Farm availability.

This definition is the probability that a Server Farm awk\appl\041479L.doc

15

20

25

30

provides access to applications and data for a particular minimum number of users. As soon as the Server Farm can not serve this particular minimum number of users, it is considered failed. When some of the users have lost connections but can reconnect to other servers and continue to work, and the majority of users do not experience any interruptions in their work, the farm is not considered failed, if it can still serve this particular number of users.

A widely used approach to improve a system's availability beyond the availability of a single system is by using Server Farms with redundant servers. In this case, if one of the farm's servers fails, the "unlucky" connected to this users server will lose their connections, but will have an opportunity to reconnect to other servers in the farm and get access to their applications and data. If all of the "unlucky" users get access to their applications and data, the farm is considered "available." If at least one of the "unlucky" users fails to get access to his/her applications and data, it means that the Server Farm's redundancy was exhausted and the Server Farm is considered failed.

The parameters for MTTF and MTTR can be estimated as indicated in the cited prior USSN 08/550,603 as a single computer virtual time between failures and a single computer virtual downtime period, respectively, for a particular application and user environment.

Therefore, the availability estimation method of the prior application USSN 09/443,926 allows one to estimate such parameters of the Server Farm as number of servers, Server Farm availability, and Server Farm

13 in sile i di 20

5

10

15

25

30

downtime, based on a set of input data. At the same time, however, this method did not provide any recommendations about optimum combinations of the Server Farm parameters that can be chosen at the Server Farm planning or design stage.

The method of the co-pending application USSN 09/474,706, entitled "Method for Server Farm Configuration Optimization" involving the Server Farm size optimization is based on the input data includes single server parameters similar to the prior application USSN 09/443,926 and at least two new extra parameters which include: single server cost and the downtime cost. Additionally, this method included newly added steps of selecting an optimization parameter, selecting an optimization criterion, and using optimization technique procedure to find the optimum value of the optimization parameter. Therefore the optimization method of the co-pending application USSN 09/474,706 allows one to find the optimum configuration of the single Server Farm. At the same time, however, this method had some technical limitations. The original assumption, that the reliability of the balancing mechanism is much higher than the reliability of single server running applications questionable if the Server Farm size exceeds 100-120 servers. This peculiar problem arises in the situation where a very large number of users L, say 10,000, 50,000 or 100,000 users are involved.

The presently described new method improves Server Farm availability by using so called Metafarms divided into several Server Farms with a workload

10

15

25

30

balancing mechanism that distributes workload as between the Server Farms and as between the servers that make up the Server Farms. The Metafarm availability definition is similar to the Server Farm availability definition. The Metafarm availability is the probability that a Metafarm provides access to applications and data for a particular minimum number of users. Therefore probability that all Metafarm Server Farms are available.

The Metafarm design unlike Server Farm design may involve a new parameter - the number of Server Farms of equal size that make up a Server Metafarm. The number of Server Farms can be used as one of the Server Metafarm optimization parameters.

While the present invention may be shown in a preferential embodiment for a Metafarm that uses any workload balancing mechanism, it is not limited thereto, and can be used for any other data processing environment where the definition of the "Metafarm and Server Farm availability" can be applied.

Thus the object of the present invention is to provide a method for optimizing the Server Metafarm for delivery of service to this large number of users by balancing a number of Server Farms and their availability requirements. The method uses the fact that the decomposition of the Metafarm into several Server Farms can increase the Server Metafarm availability. The method will generate an optimum recommendation for the selected set of input data. For example, the input data can include parameters of the particular server that is used Metafarm building block and Server Metafarm availability can be selected as optimization criterion.

In this case, the optimum Server Metafarm configuration can include the values of the number of Server Farms of equal size that make up a Server Metafarm and the number of servers in each Server Farm.

The method of generating such optimum configurations for this type of network involving large number of users "L" is described and developed in the succeeding exposition hereinbelow.

10

15

20

25

30

SUMMARY OF THE INVENTION:

In accordance with the present invention, a novel estimator program performs method steps for the Server Metafarm optimization for a given particular large number of Metafarm users/clients "L" by balancing a number of separate Server Farms and their availability requirements. By the optimization of the Metafarm is herein meant the process of finding the optimum values of the selected optimization parameters (such as a number of Server Farms and/or a Redundancy Factor value) that deliver the optimum value (for the selected optimization criterion (such as Server Metafarm availability) and a given set of input data.

System performance in a Server Metafarm computing environment involves a particular number of concurrent users with the minimum required application response time and reliable access to their applications and data. Server Metafarm availability is the probability Server Metafarm provides a that a required performance level. A Server Metafarm parameter that indirectly defines the Server Metafarm availability and performance is designated as a Redundancy Factor, that is measure ο£ the available system resources. The Redundancy Factor involves a difference between the maximum required performance and the nominal performance as a percentage of the maximum performance.

In one particular embodiment, the method uses a simplified Server Metafarm availability model. The model uses Server Metafarm availability as an optimization criterion. The Redundancy Factor and the number of Server

10

15

20

25

Farms that make up the Metafarm are used as optimization parameters.

The method uses the fact that the decomposition of the Metafarm into several Server Farms can increase the server Metafarm availability.

BRIEF DESCRIPTION OF THE DRAWINGS:

Fig. 1 is a drawing of a data processing system which includes an application Server Metafarm that application programs for multiple clients executes (users). This is an example of the typical system where the optimization method of balancing a number of Metafarm availability requirements Server Farms and canbe applied;

Fig. 2 shows an example of the optimization criterion as a function of one of the optimization parameters for a particular value of the second optimization parameter. Here, the optimization criterion is a Metafarm Availability and optimization parameters are a number of Metafarm Server Farms and a Redundancy Factoris;

Fig. 3 shows an example of the optimization criterion as a function of one of the optimization parameters for a particular value of the second optimization parameter. Here, the optimization criterion is a Metafarm MTTF and optimization parameters are a number of Metafarm Server Farms and a Redundancy Factor;

Fig. 4 is a flow chart which shows an estimator program, which performs method steps for estimating the optimum value of two of the possible optimization

parameters of an operating Server Metafarm designed to serve a particular overall number of clients "L".

GLOSSARY LIST OF RELEVANT ITEMS:

- 1. <u>AVAILABILITY</u>: This is a measure of the readiness of the system and an application to deliver an expected service to the user with a required performance level.
- 5 It may be described as a percentage of time that a system and an application are running as distinguished from the system being down for maintenance or repairs.
 - 2. MEAN TIME TO FAILURE (MTTF): This is the average operating time between two failures, that can be estimated as the total operating time divided by the number of failures.
 - 3. MEAN TIME TO REPAIR (MTTR): This is the average "downtime" in case of failure, that can be estimated as the total downtime divided by the number of failures.
- The downtime or repair time for a single 15 DOWNTIME: application server is the time interval required to restore the server and system back to normal business the operation. At the endof repair period applications running on the repaired server are available to users. The downtime for a Server Farm is the time 20 interval required to restore the nominal Server Farm performance.
- 5. ESTIMATOR PROGRAM: This is a program which performs method steps for estimating system parameters such as the availability of application programs running on any computer, server cluster, or server farm. This type of estimator program was the subject of co-pending

10

15

applications USSN 550,603 and USSN 09/443,926, which are incorporated herein by reference.

- 6. <u>SERVER METAFARM or METAFARM</u>: This designates a group of identical Server Farms (see definition of the Server Farm below) that uses a workload balancing mechanism that distributes requests for services or applications to the available servers.
- This designates a group of identical 7. SERVER FARM: servers wherein each server provide individual service to many single individual clients. The Server Farm can run enterprise class client/server applications (SAP, PeopleSoft, Microsoft SQL) or applications that are traditionally run on a single workstation (Microsoft Office 97). The Server Farm usually uses a workload for distributes requests balancing that mechanismservices or applications to the available servers.
- 8. REDUNDANCY FACTOR (Rf): This is a measure of the additional number of users that can be added to the nominal number of users per server without exceeding the 20 maximum number of users per server (server performance benchmark maximum of users). It is a difference between maximum and nominal performance as a percentage of the maximum performance. The Redundancy Factor can be calculated as 100 percent minus a usage factor Uf.
- 25 9. SERVER FARM AVAILABILITY CALCULATOR: This is an estimator program which estimates the availability for the Server Farm.

10

- THIN CLIENT SERVER FARM AVAILABILITY CALCULATOR: 10. This is one of the examples of the SERVER FARM thin-client AVAILABILITY CALCULATORS. Because configurations are intended to make applications available to multiple users at the same time, this calculator calculates the availability of a specified number of instances of an application (not just a single instance) where each application instance is being run at the server, but all the user input response is taking place at the client terminal. In this scenario, downtime occurs whenever the number of available instances of the application drops below the required specified number of instances.
- 11. <u>USAGE FACTOR (Uf)</u>: This is the ratio of the nominal number of users per server to the maximum number of users per server (server performance benchmark maximum of users) times 100 percent.
- 12. OPTIMIZATION CRITERION: This is a function that determines the value of one of the essential system 20 attributes and must be minimized (or maximized) by variation of one or more system parameters that are chosen as OPTIMIZATION PARAMETERS. Each optimization parameter should have a predefined domain that defines the values that the optimization parameter may assume.

 25 The OPTIMIZATION CRITERION is a focus of an optimum
 - The OPTIMIZATION CRITERION is a focus of an optimum system design or configuration. Examples of the optimization criteria are system performance, system availability, and cost of ownership.

	13.	$M_{\mathbf{A}}$	=	Metafarm Availability
	14.	M _{MTTF}	=	Metafarm Mean Time to Failure (MTTF)
	15.	K	=	Number of Server Farms in the Metafarm.
5	16.	N	=	Number of Servers in the Server Farm
	17.	P	=	Maximum number of concurrent users per server or single server application performance benchmark
10	18.	L	=	Total number of users being serviced by the Metafarm, $L=K*N*P$

10

15

30

DESCRIPTION OF PREFERRED EMBODIMENT:

As seen in Fig. 1, there is illustrated a schematic drawing of a Server Metafarm 8 that consists of a number of Server Farms. These Server Farms will involve a series of Farms designated 10A, 10B, 10C,...,10K.

As a typical example, the Server Farm 10A involves a multiple number of servers designated A1, A2, A3,...,AN. Each of these servers has their own individual application programs respectively shown as 10PA1, 20PA2,...,N0PAN.

Likewise, each of the other Server Farms 10B, 10C, etc., has similar sets of hardware servers. For example, the Server Farm 10K of Fig. 1 has a set of servers designated K1, K2,...,KN, and these servers respectively have their own programs 10PK1, 20PK2,..., KOPKN.

A network 60 connects client terminals designated 1,2,...,L to enable connections to each server in the Server Metafarm. Additionally, each Server Farm has a database unit designated such as 12A for the Server Farm 10A. Likewise, the Server Farm 10K has a database unit designated 12K.

The network bus 60 of Fig. 1 provides 25 connections from the multiple number "L" of client terminals shown as client terminal 1, 2, . . . L.

It should be understood here that this type of situation with the use of a Metafarm involves a large number of client users L, such as 10,000, 50,000, or 100,000 and so on. This is the reason that a Server

10

15

20

25

30

Metafarm, such as Server Metafarm 8, requires multiple numbers of Server Farms, such as 10A, 10B, 10C,...,10K.

One of the major problems that arises in optimizing a configuration for a given total number of users L, is to decide how many Server Farms K of equal size N should be used to constitute the entire Server Metafarm, where N = the number of Servers in a Server Farm.

As was illustrated in USSN 09/474,706, Redundancy Factor is a key parameter in estimating Server Farm availability since it defines Server Farm size. The Redundancy Factor was used as one of the optimization parameters for the optimum Server Farm configuration. The definition of the Redundancy Factor can be applied to Metafarms also. For example, if a Metafarm should serve a large number of users where L=30,000 (Metafarm users) and each of the servers that make up this Metafarm can serve P=100 users, then a Metafarm size K=1 (it is just one farm) and a Server Farm size N (that is a minimum number servers that can serve L users) is equal N=30,000/100=300 servers. This Metafarm does not have any redundant servers. According to the Metafarm availability definition, if any of the 300 servers fails, the Metafarm will be considered failed. To improve the Metafarm availability, redundant servers can be added. In case of the Redundancy Factor Rf=10%, the Metafarm resources to serve about 3,000 additional users are considered redundant. In terms of servers, it is about 30 additional servers. (30 is 10% of 300). Unfortunately, the original assumption (made in USSN 09/474,706) that the reliability of the Server Farm workload balancing mechanism is much

higher than the reliability of a single server running applications becomes questionable if the Server Farm size exceeds 100-120 servers. This is why the novel method described here uses the decomposition of the Metafarm into several Server Farms. The Metafarm can be divided into different number of the identical Server Farms with the same number of servers per Server Farm. The redundant servers can then be distributed evenly between Server Farms.

- The goal of the reliable Metafarm design is to find a configuration with a minimum number of Metafarm servers (optimum configuration) that meets two major requirements:
- performance requirement: to serve a given
 large number of users L;
 - 2) availability requirement: provide a given Metafarm Availability value M_A or a given Metafarm MTTF value M_{MTTF} .

Two optimization parameters that define the 20 optimum configuration are the number of Server Farms K that make up the Metafarm and the Redundancy Factor that defines the overall number of servers.

Fig. 2 illustrates an example of the Metafarm optimization. Fig. 2 is a graphical plot of availability against the number "K" of Server Farms for a specified range of Redundancy Factors. The data used for optimization include the following:

a) performance requirement: provide services for L=30,000 users;

10

15

20

25

- b) availability requirement: provide Metafarm Availability $M_A=0.999999$;
- c) single server that runs application programs MTTF=1,500 hours;
- d) single server that runs application programs MTTR=6 hours;
 - e) single server that runs application programs performance benchmark P=100 concurrent users;
 - f) Redundancy Factor domain is an interval (10%, 14%);
 - g) Number of Server Farms is a natural number 1, 2, . . . 10.

There are three configurations on Fig. 2 with availability M_A that is greater or equal 0.99999. configurations are for a Redundancy Factor that is equal to Rf=14% (where the First configuration includes 345 servers that are distributed between 3 server farms. Each server farm contains 115 servers where 14 servers are considered redundant servers. The second configuration includes 344 servers that are distributed between 4 server farms. Each server farm contains 86 servers where 10 servers are considered redundant servers). The third configuration is for a Redundancy Factor that is equal to Rf=13%. (This third configuration includes 342 servers that are distributed between 3 server farms. Each server farm contains 114 servers where 13 servers are considered redundant servers). It is obvious, that the configuration with the smaller value of the Redundancy Factor Rf=13% and three Server Farms is the optimum configuration for

10

15

20

25

this example, because it requires less servers than the two other configurations.

Fig. 3 illustrates the same example of the Metafarm optimization where the availability requirement is given in the form of the Metafarm MTTF value where M_{MTTF} is equal to 600,000 hours. Again, there are three configurations on Fig. 3 with Metafarm MTTF that greater than orequal to 600,000 hours. Two configurations are for a Redundancy Factor Rf that is equal to 14% and one configuration is for a Redundancy Factor Rf that is equal to 13%. The value of the Metafarm MTTF for 3 Server Farms and Redundancy Factor Rf=14% is equal to 1,843,768 hours and is not shown in Fig. 3 due to limited graph size. The optimum configuration is the same as for the availability requirement in the form of the Metafarm Availability value that is equal to 0.99999: so that 3 Server Farms with the Redundancy Factor Rf 13% is seen to have the least number of servers that deliver MTTF that is greater than the required goal (600,000 hours).

Now, in accordance with the present invention, steps are provided for optimization of a Server Metafarm designed to serve a particular large number of users "L". These steps will be described in conjunction with Fig. 4 that shows an estimator program, which performs method steps for estimating parameters of the optimum operating Server Metafarm.

In step A of Fig. 4, requests for the following input parameters are displayed: (1) performance requirement in the form of required large number of users "L" for utilizing said Server Metafarm, (2) the maximum

10

15

20

25

single-server workload "P" of concurrent users (the performance benchmark), (3) the Mean Time To Repair for a single server, and (4) Mean Time To Failure for a single server.

In step B of Fig. 4, the values of the requested input parameters are entered on the computer monitor by means of the keyboard.

In step C of Fig. 4, an optimization parameter (parameters) and its (their) domain is (are) selected. For example, in Fig. 2 and 3, the selected optimization parameters are the Number of Server farms K and the Redundancy Factor Rf. The Number of Server Farms is a natural number 1, 2, . . . 10. The Redundancy Factor domain is an interval (10%,14%) that is the interval between 0 and 100 percent.

In step D of Fig. 4, an optimization criterion selected. In Fig. 2, for example, the selected optimization criterion is the Redundancy Factor that should be minimized and, additionally, the selected constraint in the form of the minimum required Server Metafarm Availability value is the Metafarm Availability goal M_{λ} that should be greater or equal to 0.99999. Fig. 3, for another example, the selected optimization is the Redundancy Factor that should criterion minimized and, additionally, the selected constraint in the form of the minimum required Server Metafarm MTTF value is the Metafarm MTTF goal M_{MTTF} that should be greater than or equal to 600,000 hours.

In step E of Fig. 4, optimization of the 30 optimization criterion selected at step D occurs by one of the known optimization techniques described in the awk\appl\041479L.doc

15

20

25

books: Practical Optimization by Philip Gill, Academic Press, 1981 and/or Engineering Optimization: Methods and Applications by G. V. Reklaitis and others, John Wiley & Fig. 2 and 3 illustrate one of the simplest Sons, 1983. optimization techniques by the plotting of the graph for optimization parameters. values of the set of Particularly, the used values of the Number of Server Farms K that make up the Metafarm are natural numbers 1, 2, . . . 10 and the used values of the Redundancy Factor are from 10% to 14% percent with steps of 1%: as for example, 10, 11, . . . 14%. If the accuracy of the calculation is not sufficient, then the value of a step can be reduced from 1% to 0.5%, etc.

In step F of Fig. 4, the optimum values of the optimization parameters are displayed. For example, in Fig. 2 and 3, the optimum value of the Number of Server Farms K that make up the Metafarm is 3 Server Farms and the optimum value of the Redundancy Factor is 13% which corresponds to the Metafarm with 342 servers.

Described herein has been an optimization method and an estimator program for a Server Metafarm designed to serve a particular large number of clients L.

While a preferred implementation of the invention has been described, it should be understood that other implementations may be used which are still encompassed by the attached claims.

15

WHAT IS CLAIMED IS:

- 1. An estimator program that performs method steps for estimating parameters of the optimum operating Server Metafarm designed to serve a particular large number of clients L comprising the steps of:
- (a) inputting a group of parameters involving at least one Server Metafarm parameter and at least one single server parameter;
 - (b) selecting at least one Server Metafarm optimization parameter and its domain which indicates the values that the Server Farm optimization parameter may assume;
 - (c) selecting a Server Metafarm optimization criterion that is a function of said Server Metafarm optimization parameter or parameters;
 - (d) using an optimization technique to find the optimum value (values) of the optimization parameter (parameters).

10

5

- 2. The method of claim 1 wherein said step (a) of inputting said group of parameters includes the steps of:
 - (a1) selecting for input said particular number of clients "L" for utilizing said Server Metafarm;
 - (a2) selecting for input a maximum single server workload of users "P";
 - (a3) selecting for input a mean time to repair value (MTTR) for a single server;
 - (a4) selecting for input a mean time to failure (MTTF) for a single server.
- 3. The method of claim 1 wherein step (b) for selecting optimization parameters includes:
 - (b1) selecting a number of Server Farms that make up a Server Metafarm which is any natural integer number of servers wherein each Server Farm is the same size, in number of servers, as each other Server Farm.
- 4. The method of claim 1 wherein step (b) for selecting optimization parameters includes:
 - (b2) selecting a Redundancy Factor having a domain which is an interval between 0 and 100 percent.

5

- 5. The method of claim 1 wherein step (b) for selecting optimization parameters includes:
 - (b3) selecting a number of Server Farms of equal size that make up a Server Metafarm which number is any natural integer number of servers, and,
 - (b4) selecting a Redundancy Factor having a domain which is an interval between 0 and 100 percent.
- 6. The method of claim 1 wherein step (c) for selecting said optimization criteria includes:
 - (c1) selecting an optimization function which is the Server Metafarm Mean Time To Failure.
- 7. The method of claim 1 wherein step (c) for selecting said optimization criteria includes:
 - (c2) selecting an optimization function which is the Server Metafarm Availability.
- 8. The method of claim 1 wherein step (c) for selecting said optimization criteria includes:
 - (c3) selecting an optimization function which is the Redundancy Factor that should be minimized and, additionally, selecting a constraint in the form of the minimum required Server Metafarm Mean Time To Failure value.

- The method of claim 1 wherein step (c) for selecting said optimization criteria includes:
 - (c4) selecting an optimization function which is the Redundancy Factor that should be minimized and, additionally, selecting a constraint in the form of the minimum required Server Metafarm Availability value.
- 10. The method of claim 1 wherein step (d) for using said optimization procedure includes the steps of:
 - (d1) selecting a value of said
 optimization parameters from said domain;
 - (d2) calculating a value for said
 optimization criterion;
 - (d3) making an evaluation decision about the end or the continuation of said optimization procedure.
- 11. The method of claim 10 wherein step (d3) involves the decision to stop the procedure if the optimum number of Server Farms in the configured Server Metafarm is determined.

12. The method of claim 10 wherein step (d3) includes the step of:

(d3a) continuing the optimization procedure if the optimum number for each single Server Farm size is not yet determined, by repeating said step (d2) with another value of said optimization parameter (parameters) from said domain (domains).


10

ABSTRACT OF THE DISCLOSURE:

TITLE: METHOD FOR SERVER METAFARM CONFIGURATION
OPTIMIZATION

A method and a novel estimator program are provided for Server Metafarm optimization for a given particular large number of the Metafarm users/clients "L" by balancing a number of separate Server Farms and their availability requirements. By the optimization of the Metafarm is herein meant the process of finding the optimum values of the selected optimization parameters (such as a number of Server Farms and/or a Redundancy Factor value) that deliver the optimum value for the selected optimization criterion (such as Server Metafarm availability) and a given set of input data.

- **>**







Fig. 3






Fig. 4

COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:
TYPE OF DECLARATION
This declaration is of the following type:
X original
design
_ supplemental
divisional
_ continuation
continuation-in-part (CIP)
INVENTORSHIP IDENTIFICATION
My residence, post office address and citizenship are as stated below next to my name, I believe I am he original, first and sole inventor (if only one name is listed below) or an original, first and joint nventor (if plural names are listed below) of the subject matter which is claimed and for which are a patent is sought on the invention entitled:
TITLE OF INVENTION
METHOD FOR SERVER METAFARM CONFIGURATION OPTIMIZATION
SPECIFICATION IDENTIFICATION
he specification of which: (complete (a), (b) or (c))
(a) X is attached hereto.
(b) _was filed on as □ Serial No. or □ Express Mail No., as Serial No. not yet known
ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I hereby state that I reviewed and understand the contents of the above identified specification, including the claims, as amended by an amendment referred to above.

I acknowledge the duty to disclose information

- which is material to patentability as defined in 37, Code of Federal Regulations, § 1.56
- and which is material to the examination of this application, namely, information
 where there is a substantial likelihood that a reasonable examiner would consider it
 important in deciding whether to allow the application to issue as a patent, and
- __ In compliance with this duty there is attached an information disclosure statement in accordance with 37 CFR 1.98.

POWER OF ATTORNEY

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

ALFRED W. KOZAK, REG. NO. 24,265 MARK T. STARR, REG. NO. 28,762

SEND CORRESPONDENCE TO

ALFRED W. KOZAK UNISYS CORPORATION 10850 VIA FRONTERA, MS 1000 SAN DIEGO, CALIFORNIA 92127 DIRECT TELEPHONE CALLS TO: (Name and telephone number)

ALFRED W. KOZAK (858) 451-4615

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

Full name of sole or first inventor:

Lev (GIVEN NAME)	(N,M,I.) (MIDDLE INITIAL OR NAME)	Smorodinsky Family (or last name)
Inventor's signature	auro &	
Date 11/01/2000	Country of Citizenship USA	
Residence: 25121	Grissom Road, Laguna Hills, California 92653	
Post Office Address	same as above	